

ORR

series

Radiant Heater

Comfort in large spaces

The ORR series is designed to heat specific areas within large spaces. These low-inertia heaters are able to make an area comfortable in minutes. An anodized aluminum reflector allows maximum heat distribution.



TH113



church

workshop

indoor swimming pool

warehouse

Features

- Finish** - Anodized aluminum.
- Voltage** - 120V, 208V, 240V, 277V, 600V, 1-phase.
- Construction** - No visible light is emitted by the heater.
- Built-in adjustable directional system.
- 60° standard radiation angle (optional 45°).
- Heating element** - Incoloy stainless steel tubular heating element.
- Watt density** - Standard watt density of 762W/ft. (2500W/m).

- Installation** - Vertical or horizontal mounting.
- Surface mounted to connection box (on non-combustible surface) or suspended by chains and eyelets (chains not included).
- 194 °F wiring is sufficient.
- Recommended installation height: 8 to 10 ft. (2.4 to 3 m).
- Warranty** - 1-year warranty against defects.

Models

Watts	Product #				Over-all length		Heating section		Weight	
	120V	208V	240V	277V	in.	mm	in.	mm	lbs	kg
950	ORR0952	ORR0958	ORR0950	-----	31 1/2	800	20	508	6.0	2.7
1500	ORR1502	ORR1508	ORR1500	-----	43 1/2	1105	32	813	8.0	3.6
1900	ORR1902	ORR1908	ORR1900	-----	49 1/2	1257	38	965	9.0	4.1
2000	-----	ORR2008	ORR2000	ORR2077	43 1/2	1105	32	813	8.0	3.6
2300	-----	ORR2308	ORR2300	ORR2377	49 1/2	1257	38	965	9.0	4.1
3000	-----	ORR3008	ORR3000	ORR3077	61 1/2	1562	50	1270	10.0	4.5
3800	-----	ORR3808	ORR3800	ORR3877	73 1/2	1867	62	1575	12.0	5.4

To obtain a radiation angle of 45°, add "-45" to the product number.

Accessories

Product #	Description
TH113-R-024T	24V percentage timer (install with electronic relay RT850)
Wire guard (factory installed only)	
Product #	Watts
ORR-GP1	950
ORR-GP2	1500/2000
ORR-GP3	1900/2300
ORR-GP4	3000
ORR-GP5	3800

