

# OVR series

## Residential Register Heater

The OVR fan-forced heater is designed for areas with limited space. This high-efficiency heater is equipped with a silent axial fan that blows air over a high quality heating element, thus producing warm air circulation throughout the room. Whether installed in horizontal position, its design will match perfectly with all interior styles.



hallway

basement

kitchen

bathroom

stairwell

### Features

- Color
  - Standard: white, almond.
  - Optional and custom colors available upon request.
- Finish
  - Standard: epoxy/polyester powder paint.
- Voltage
  - 120V, 208V, 240V/208V, 1-phase.
- Construction
  - 20-gauge steel.
  - High-limit temperature control with automatic reset.
- Fan
  - Quiet fan operating at 38 dBA (500W to 1000W; 40 cfm fan) and 41.3 dBA (1250W to 2000W; 80 cfm fan).
  - Factory-lubricated motor.
- Heating element
  - Durable tubular heating element with fins.
- Control
  - Built-in thermostat available with a control knob or tamperproof adjustable with a screwdriver.
- Installation
  - The air outlet should be installed 10 in. (25.4 cm) above floor.
  - Large wiring compartment.
  - May be recessed in 2 in. x 3 in. stud partitions.
  - Surface mounting box available.
  - Quick installation with recess box mounting holes.
  - Tight fit with V-shaped recess box.
  - The air outlet should be installed 10 in. (25.4 cm) above floor.
- Warranty
  - 1-year warranty against defects.

### Standard Models

Product #	Volts	Watts	Weight	
			lbs	kg
OVRU0502	120	500	9.0	4.1
OVRU0752	120	750	9.0	4.1
OVRU1002	120	1000	9.0	4.1
OVRU1252	120	1250	9.0	4.1
OVRU1502	120	1500	9.0	4.1
OVRU0500	240/208	500/375	9.0	4.1
OVRU0750	240/208	750/563	9.0	4.1
OVRU1000	240/208	1000/750	9.0	4.1
OVRU1250	240/208	1250/938	9.0	4.1
OVRU1500	240/208	1500/1125	9.0	4.1
OVRU2000	240/208	2000/1500	9.0	4.1
OVRU2008	208	2000	9.0	4.1

Add "BL" for white, "AM" for almond.

### Accessories

Product #	Description
OVR-TB1	Single-pole thermostat kit 17A
OVR-TB1-AV	Single-pole tamperproof thermostat kit 17A
OVR-TB2	Double-pole thermostat kit 17A
OVR-TB2-AV	Double-pole tamperproof thermostat kit 17A
OVR-BS	Surface mounting box
OVR-DIS*	Disconnect switch 277V max. 20A

\* Factory installed

