OHY Convection and Fan Heater









Training available online www.ouellet.com

Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

• Standard: epoxy/polyester powder paint.

Voltage

• 240V, 1-phase.

Construction

- Cast aluminum front cover.
- Steel bar grilles prevent the insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- · Automatic reset safety device.
- Built-in white LED night light. 1

- · Whisper-quiet squirrel-cage fan.
- Factory-lubricated motor.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Control

- Built-in electronic digital thermostat/timer. 2
- Thermostat mode: pulse modulation: automatic convection to fan-forced switch-over at 1000W.
- Timer mode: 5-30 minutes full power fan-forced boost. 3

Installation

- 4 in. (102 mm) minimum clearance to floor.
- May be surface-mounted or recessed in 2 in. X 3 in. stud partitions.
- Mounting holes for ease of installation.
- Large wiring compartment.

• 5-year warranty against defects.

Application

• Bathroom, kitchen, family room, entrance way.

Model

Watts	Volts	Product #	Price	Weight	
				lb	kg
2000¹	240	OHY2000-TH ¹	773.00	22.75	10.3

Option

Product # Kit	Product # Factory installed*	Price	Description
KIT-OHY-DIS ²	DIS ²	112.00	Disconnect switch, 20A at 250V

* For factory installed options, add the option number to the product number.

See the **Product Code** section inside the front cover.

BEWARE: Not available for 208V.

² For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

Add"BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section. Electronic thermostat available in grey only.



