

OHV-RF Hard-Wired Unit Heater



Features

Color

- Standard: almond and black.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1 phase.

Construction

- Positive off, double-pole, single-throw thermostat.
- Fan on/auto switch.
- Two level finger-tip high/low heat selector switch.
- Automatic reset over temperature protector.
- Specially designed outlet diffuser provides maximum air velocity and prevents foreign objects from entering heater.
- 18 and 20 gauge steel.
- Motor - totally enclosed - thermally protected.
- Draw-through design permits greater heat transfer.

Installation

- Minimum mounting height of 6 ft. (1.8 m).
- Maximum mounting height of 10 ft. (3 m).
- Versatile bracket for ceiling or wall mounting.
- Adjustable bracket allows all angle rotation.
- Large and easily accessible wiring compartment.

Note: We recommend installing this product on an outside ceiling or wall to avoid vibrations spreading to an adjacent room.

Warranty

- 1-year warranty against defects.

Application

- Factory, garage, school.

Model

Product # ¹	Volts	Phase	kW	Amp.	Air Flow		Temperature Rise		Weight	
					fpm	cfm	°C	°F	lb	kg
OHVU05000AMRF-F1-HL-T5	240/208	1	5/3.75	20.8/18	800	310	28	51	42	19

¹ Units come standard with hi-lo heat setting, fan only switch, integral thermostat and combination wall/ceiling mounting bracket. Standard color is almond and black.

