



Olympia Ductless Single Zone
Heat Pump
OTP-O Series

Why choose a Ductless Wall-Mounted Heat Pump?

Ductless wall-mounted heat pumps, commonly known as “mini split” heat pumps, do not need air ducts like central systems. The outdoor unit (condenser) and the indoor unit (evaporator) are connected by refrigerant piping and electrical wires that pass through a small 3” opening in the wall.

Single zone

A single zone system consists of an outdoor unit connected to an indoor unit. This system is ideal for providing heating and air conditioning to a predefined area, such as an openconcept kitchen/living room or a family room in the basement.

Indoor Unit

- Plastic housing, standard white.
- 7-speed cross-flow fan (auto, turbo, high, medium-high, medium, low and very low).
- Easy to dismantle for maintenance.
- Washable filters.

Outdoor Unit

- Variable speed rotary compressor (INVERTER), with overload protection.
- Compressor blanket and preheating technology.
- Quiet axial-flow fan.
- Condenser fins covered with a hydrophilic coating for improved corrosion resistance.

Performance up to




Cooling



Heating

Up to



Features and functions



Smart Pan Heater

Prevents ice formation in the base pan of the outdoor unit.



Compressor Blanket and Preheating Technology

Keeps the oil inside the compressor warm and prevents it from mixing with the refrigerant.



Anti-Corrosion Fin Coating

Condenser and evaporator fins are covered with a hydrophilic coating for greater corrosion resistance – a clear advantage for people living in coastal regions.



Quiet Design

The innovative axial fan design and the strengthened motor bracket minimize vibrations and outside noise levels. The integrated rear base and evaporator make our indoor units some of the quietest on the market.



Smart Defrosting

Provides greater comfort and energy savings by eliminating unnecessary defrost cycles.



Smart Preheating

The system delays turning on the fan in heating mode to avoid blowing cold air out at startup.



Auto Restart

In case of power failure, user selection and system parameters are stored in non-volatile memory. The system will automatically return to the last operating mode when power resumes.



Auto-Clean

After the heat pump turns off, the fan continues to operate until the indoor unit is completely dry to prevent mold growth.



Self-Diagnosis

A microcomputer monitors the system and turns the unit off if abnormal operation is encountered. An error code will be displayed on the indoor unit to facilitate maintenance.



Sleep Mode

This function can be used to gradually increase or decrease room temperature, so you can save energy without affecting your sleep.



Turbo Mode

The unit operates at super high speed to achieve quick cooling or heating.



Up & Down Swing

Can be used to select oscillating angles for the horizontal louvres. Choose a fixed positions or use the auto swing mode to swing the louvres up and down in all positions.



Left & Right Swing

Can be used to select oscillating angles for the vertical louvres. Choose a fixed positions or use the auto swing mode to swing the louvres left and right in all positions.



Timer

Allows you to program the time you want the unit to start and stop over a 24-hour period.



I Feel

This function allows you to use the remote controls an ambient sensor.



Lock

This function disables unwanted temperature adjustments and the use of different modes on the device.



Wi-Fi

Use your phone, tablet or computer to control your unit, wherever you are (Internet connection required).



**10-year basic warranty
parts and compressor**

Models

Product # ¹	Indoor Unit Outdoor Unit		UHD09KCH38SB-I UHD09KCH38SB-O	UHD12KCH31S-I UHD12KCH31S-O	UHD18KCH25S-I UHD18KCH25S-O	UHD24KCH22S-I UHD24KCH22S-O
Technical Performance						
Voltage		Volts	230/208	230/208	230/208	230/208
Cooling capacity	Nominal	W (BTU/hr)	2638 (9000)	3517 (12000)	5276 (18000)	6450 (22000)
	Min. – max.	W (BTU/hr)	450 - 3800 (1535 - 12966)	850 - 4500 (2900 - 15354)	1200 - 6400 (4094 - 21837)	2000 - 9000 (6800 - 30700)
Heating capacity	Nominal	W (BTU/hr)	2638 (9000)	3575 (12200)	5276 (18000)	7000 (24000)
	Min. – max.	W (BTU/hr)	700 - 4000 (2388 - 13648)	900 - 5500 (3071 - 18766)	1200 - 7200 (4094 - 24566)	2000 - 9500 (6800 - 32000)
Used cooling power input	Nominal	W	540	785	1330	1700
	Min. – max.	W	50 - 1400	75 - 1500	350 - 2500	450 - 3700
Used heating power input	Nominal	W	590	940	1500	2000
	Min. – max.	W	200-1500	250 - 1600	350 - 2500	380 - 3700
Used rated input		W	1500	1600	2500	3700
Rated current		A	6.2	6.5	10.8	16.4
MCA		A	9	9	22	22
Max. over-current protection (MOCP)		A	15	15	30	35
SEER		-	38	30.5	24.5	21.5
HSPF		-	15	14	12	12
EER		W/W	4.84	4.48	3.97	3.81
COP		W/W	4.47	3.8	3.52	3.5
AHRI number		-	202110483	202110484	202110485	202132789
ENERGY STAR		-	✓	✓	✓	✓
Indoor Unit						
Dehumidification		pt/hr (l/hr)	1.69 (0.80)	2.96 (1.40)	3.80 (1.80)	4.23 (2)
Air flow volume	T / H / MH / M /		424 / 383 / 353 / 324 /	500 / 471 / 441 / 353 /	736 / 677 / 618 / 559 /	824 / 765 / 706 / 647 /
	ML / L / Q ²	cfm	294 / 265 / 206	324 / 265 / 235	500 / 457 / 353	589 / 500 / 383
Sound level	T / H / MH / M /		43 / 40 / 38 / 36 /	49 / 46 / 43 / 40 /	51 / 48 / 45 / 42 /	52 / 49 / 46 / 43 /
	ML / L / Q ²	dB (A)	33 / 31 / 19	37 / 34 / 22	39 / 36 / 34	40 / 37 / 34
Fan motor power output		W	60	60	60	70
Fan motor RLA		A	0.09	0.09	0.24	0.38
Deflector stepper motor power output		W	2.5 / 1.5	2.5 / 1.5	2.5 / 1.5	2.5
Net weight		lb (kg)	29.8 (13.5)	29.8 (13.5)	36.4 (16.5)	36.4 (16.5)
Outdoor Unit						
Air flow volume		cfm	2400	2400	2354	4000
Sound level		dB (A)	53	53	59	59
Compressor power input		W	1070	1070	2443	2443
Compressor LRA		A	35	35	30	30
Compressor RLA		A	6.9	6.9	15.5	16
Fan motor power output		W	30	30	90	90
Fan motor RLA		A	0.24	0.24	0.65	0.65
Refrigerant volume (R410A)		oz (g)	45.9 (1301)	49.4 (1400)	70.6 (2101)	81.1 (2299)
Net weight		lb (kg)	99.2 (45)	99.2 (45)	141.1 (64)	147.7 (67)
Operating ambient temperature	Cooling	°C (°F)		-18 to 54 (0 to 129)		
	Heating	°C (°F)		-30 to 24 (-22 to 75)		
Connection Piping/Refrigerant						
Pre-charge length		ft. (m)	25 (7.5)	25 (7.5)	25 (7.5)	25 (7.5)
Additional refrigerant charge		oz/ft. (g/m)	0.2 (20)	0.2 (20)	0.5 (50)	0.5 (50)
Liquid pipe outer diameter		in.	1/4	1/4	1/4	1/4
Gas pipe outer diameter		in.	1/2	1/2	5/8	5/8
Maximum height difference		ft. (m)	49 (15)	49 (15)	66 (20)	98 (30)
Maximum total length		ft. (m)	98 (30)	98 (30)	100 (30)	164 (50)

¹ 1 indoor unit and 1 outdoor unit. Note that each unit is individually packaged.

² Cross-Flow Fan Speeds: (T) Turbo / (H) High / (MH) Medium-High / (M) Medium / (ML) Medium-Low / (L) Low / (Q) Quiet.