





## Features

### Color

- Standard: bronze, white, almond.
- Optional (upcharge applicable): metallic silver,
- metallic charcoal, aluminum, semi-gloss black, sand. • Custom colors available upon request.

#### Finish

• Standard: epoxy/polyester powder paint.

### Voltage

• 120V, 240/208V, 1-phase.

### Construction

- Welded 20-gauge steel.
- Sturdy floor grille (14-gauge).
- Protective screen keeps foreign objects from falling into the unit.
- High-limit temperature control with manual reset.

# **Models**

Product #	Volts	Watts	Weight	
			lb	kg
OFH0502	120	500	16.0	7.3
OFH1002	120	1000	16.0	7.3
OFH1502	120	1500	16.0	7.3
OFH0500	240/208	500/375	16.0	7.3
OFH1000	240/208	1000/750	16.0	7.3
OFH1500	240/208	1500/1125	16.0	7.3

Add "BZ" for bronze, "BL" for white, "AM" for almond.

Optional colors shown in the color chart section are available upon request.

#### Fan

- Large diameter, quiet fan operating at 43.9 dBA at 80 cfm.
- Factory-lubricated motor.

#### Heating element

• Durable tubular heating element with fins.

#### Installation

- Minimum clearance from adjacent walls: 6 in. (15.2 cm).
- Large wiring compartment.

# Warranty

1-year warranty against defects.

## Application

• Bay window, near patio door.

Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.

