

**OCC** Portable Construction Heater

**OCC-WB** Unit Heater with Bracket

**OCC-RF** Hard-Wired Unit Heater



Grounded 3-Pronged Outlet (OCC, OCC-WB)



NEMA 6-30R  
30A, 250VAC

## Features

### Color

- Standard: almond.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 240/208V, 1-phase.

### Construction

- Handle may be used as a reel for the electric cable and as attach point for the bracket.
- 6 ft. (2 m) molded electric cable.
- Safely recessed thermostat knob reduces heater size to a minimum.

- High-limit temperature control with automatic reset.

### Fan

- 300 cfm fan.

### Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

### Temperature rise

- 28 °C (51 °F).

### Control

- Built-in thermostat included.

## Features OCC

### Fan

- Totally enclosed motor (-MF model).
- Open motor (-MO model).

*Note: The open motor is not intended for use in a dusty environment.*

### Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

*Note: Always unplug heater when not in use.*

### Warranty

- 2-year warranty against defects (-MO model).
- 3-year warranty against defects (-MF model).

### Application

- Construction area, workshop, garage

## Features OCC-WB

### Fan

- Open motor.

*Note: The open motor is not intended for use in a dusty environment.*

### Installation

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.
- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

*Note: Always unplug heater when not in use.*

### Warranty

- 2-year warranty against defects.

### Application

- Workshop, shed, garage.

## Features OCC-RF

### Fan

- Open motor.

*Note: The open motor is not intended for use in a dusty environment.*

### Installation

- Hard-wired into an electrical junction box (not included).
- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.

### Warranty

- 2-year warranty against defects.

### Application

- Workshop, shed, garage.

## Models

Watts	Volts	Product # <sup>1</sup>	Price	Motor type	Grounded 3-pronged outlet	Weight lb kg
4800/3600	240/208	OCC4800AM-MF-TB6	254.00	Enclosed	30A, 250VAC	16.0 7.3
4800/3600	240/208	OCC4800AM-MO-TB6	187.00	Open	30A, 250VAC	16.0 7.3
4800/3600	240/208	OCC4800AMWB-MO-TB6 <sup>1</sup>	245.00	Open	30A, 250VAC	16.0 7.3
4800/3600	240/208	OCC4800AMRF-MO-TB6 <sup>1</sup>	228.00	Open	-	16.0 7.3

<sup>1</sup> Mounting bracket included.  
Standard color is almond.

