OCC-WB Unit Heater with Bracket





NEMA 6-30R 30A, 250VAC



Features

Color

• Standard: almond.

Finish

• Standard: epoxy/polyester powder paint.

Voltage

• 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electrical cable.
- 6 ft. (2 m) molded electrical cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- $\bullet \ \ \ High-limit\ temperature\ control\ with\ automatic\ reset.$

Far

- Open motor permanently lubricated (-MO model). 1
- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat

Temperature rise

• 28 °C (51 °F).

Control

• Built-in thermostat included.

Installation

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.
- Must be plugged into a grounded 3-pronged outlet, 30A, 240VAC. 2

Warranty

• 2-year warranty against defects.

Application


• Workshop, shed, garage.

Models

	Watts	Volts	Product #1	Price	Motor type	Grounded 3-pronged outlet	Weight	
							lb	kg
	4800/3600	240/208	OCC4800AMWB-MO-TB6 ¹	260.00	Open	30A, 240VAC	16.0	7.3

¹The open motor is not intended for use in a dusty environment.

Standard color is almond.



² Always unplug heater when not is use.