



Features

Nominal voltage

- 120V.

Linear density

- 5 Watts per foot.

Cold lead length

- 30 in. (0.76 m).

Outer jacket

- PVC.

Bus wire

- Nickel plated copper.

Minimum bend radius

- 1/2 in. (12 mm).

Included hardware

- Roof clips for cable and spacers.
- Grounded 3-pronged plug with indicator light to show when the cable is on.

Installation

- **Never cut or shorten the heating cable.**
- For residential outdoor applications only.
- Minimum installation temperature: 0 °C (32 °F).

Warranty

- 1-year basic warranty on the heating cable.

Application

- Roof and gutter de-icing.

Models

Product # ¹	Price	Length		Watts
		ft.	m	
ORF-R020	63.00	20	6.1	100
ORF-R030	74.00	30	9.1	150
ORF-R060	81.00	60	18.3	300
ORF-R080	100.00	80	24.4	400
ORF-R100	106.00	100	30.5	500
ORF-R120	124.00	120	36.6	600
ORF-R140	139.00	140	42.7	700
ORF-R160	151.00	160	48.8	800
ORF-R180	175.00	180	54.9	900
ORF-R200	182.00	200	61.0	1000
ORF-R240	195.00	240	73.2	1200

¹ Must be plugged into a 120V outlet fitted with ground fault protection device (GFCI).

Options

Product #	Price	Description
KIT-RF-CLIP	9.00	Roof clips (25) and spacers (15) for constant wattage heating cables
RCR-U	138.00	Roof and gutter sentry for automatic de-icing control with humidity probe