

OCC Portable Construction Heater



NEMA 6-30R
30A, 250VAC



Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electrical cable.
- 6 ft. (2 m) molded electrical cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset.

Fan

- Enclosed motor permanently lubricated (-MF model).
- Open motor permanently lubricated (-MO model). ¹
- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat

Temperature rise

- 28 °C (51 °F).

Control

- Built-in thermostat included.

Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 240VAC. ²

Warranty

- 2-year warranty against defects (-MO model).
- 3-year warranty against defects (-MF model).

Application

- Construction area, workshop, garage.

Models

Watts	Volts	Product # ²	Price	Motor type	Grounded 3-pronged outlet	Weight lb kg	
4800/3600	240/208	OCC4800AM-MF-TB6	270.00	Enclosed	30A. 240VAC	16.0	7.3
4800/3600	240/208	OCC4800AM-MO-TB6 ¹	199.00	Open	30A. 240VAC	16.0	7.3

¹ The open motor is not intended for use in a dusty environment.

² Always unplug heater when not in use.

Standard color is almond.

