

OCC Portable Construction Heater



Grounded 3-Pronged Outlet



NEMA 6-20R
20A, 250VAC



NEMA 6-30R
30A, 250VAC

Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electrical cable.
- 6 ft. (2 m) molded electrical cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset (first level) and single operation thermal fuse (second level).

Fan

- Open motor permanently lubricated (-MO model). ¹
- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Temperature rise

- 28 °C (51 °F).

Control

- Built-in thermostat included.

Installation ²

- 4000W must be plugged into a grounded 3-pronged outlet, 20A, 240VAC.
- 4800W must be plugged into a grounded 3-pronged outlet, 30A, 240VAC.

Warranty

- 2-year warranty against defects.

Application

- Construction area, workshop, garage.

Models

Product #	Volts	Watts	Motor type	Grounded 3-Pronged Outlet	Weight	
					lb	kg
OCCU4000AM-MO-TB6 ¹	240/208	4000/3000	Open	20A, 240VAC	16.0	7.3
OCCU4800AM-MO-TB6 ¹	240/208	4800/3600	Open	30A, 240VAC	16.0	7.3

¹ The open motor is not intended for use in a dusty environment.

² Always unplug heater when not in use.

Standard color is almond.

