



## OCL Series Standard Convectector



**Modern, simple and discreet design**

To match any decor

**Optimum heat efficiency**

Top air outlet for rapid, even heat distribution throughout the room

**Slimmer profile**

Saves space with a more compact convectector

**Natural convection**

Offering a whisper-quiet machine





**Built-in electronic thermostat in option**

Simple and easy to use

## Models

Volts	Watts	Product #		Length		Weight	
		Without thermostat	Built-in thermostat	in.	mm	lb	kg
120	500	OCLU0502BL	OCLU0502BL-TH	18	457	13	6
120	1000	OCLU1002BL	OCLU1002BL-TH	23 9/16	598	16.7	7.6
120	1500	OCLU1502BL	OCLU1502BL-TH	29 1/16	739	20	9.12
208	500	OCLU0508BL	OCLU0508BL-TH	18	457	13	6
208	1000	OCLU1008BL	OCLU1008BL-TH	23 9/16	598	16.7	7.6
208	1500	OCLU1508BL	OCLU1508BL-TH	29 1/16	739	20	9.12
208	2000	OCLU2008BL	OCLU2008BL-TH	34 5/8	880	24	10.9
240/208	500/375	OCLU0500BL	OCLU0500BL-TH	18	457	13	6
240/208	1000/750	OCLU1000BL	OCLU1000BL-TH	23 9/16	598	16.7	7.6
240/208	1500/1125	OCLU1500BL	OCLU1500BL-TH	29 1/16	739	20	9.12
240/208	2000/1875	OCLU2000BL	OCLU2000BL-TH	34 5/8	880	24	10.9
277	500	OCLU0577BL	-	18	457	13	6
277	1000	OCLU1077BL	-	23 9/16	598	16.7	7.6
277	1500	OCLU1577BL	-	29 1/16	739	20	9.12
277	2000	OCLU2077BL	-	34 5/8	880	24	10.9
480	1000	OCLU1004BL	-	23 9/16	598	16.7	7.6
480	1500	OCLU1504BL	-	29 1/16	739	20	9.12
480	2000	OCLU2004BL	-	34 5/8	880	24	10.9