

HP6000ZB-GE

Ductless heat pump interface



FCC15 Standard Compliant
NMB-003 Standard Compliant



Remote access requires an Internet connection
and a GT130 smart gateway (not included).

Features

Type

- Ductless ACD heat pump smart interface¹.

Color

- Standard: black.

Power supply

- Connect to the Wi-Fi port on the main board of the indoor unit.

Control

- Protocol: Zigbee 3.0.
- Frequency: 2.4 GHz.
- Transmission power: +20 dBm.
- Receiver sensitivity: -108 dBm.
- Encryption key: AES-128.

Temperature range

- 0 °C (32 °F) to 40 °C (104 °F).

Display

- Cool, Heat, Dry, Fan and OFF.
- Adjustment of the orientation of the louvers.
- Adjustment of the fan intensity.
- Activation or deactivation of the display.
- Create custom automations.
- Advanced features in Neviweb and Sinopé Smart Systems².
- Programmation fonctions are available via Neviweb and require a GT130 smart gateway.

Installation

- Connect the interface to the RJ45 type Wi-Fi port of the heat pump indoor unit main board.

Application

- ACD ductless heat pump¹.

Warranty

- 3-year warranty against defects.

¹ Available with selected models only.

² Require the use of the GT130 smart gateway, an Internet connection and a Zigbee smart thermostat OTH4000-ZB.

Models

Product #	Price	Description
HP6000ZB-GE ¹	90.00	Ductless ACD heat pump smart interface
GT130	122.00	Smart gateway that provides remote access to the HP6000ZB-GE

¹ Requires the use of the GT130 smart gateway.

Standard color is black