

# DS-2C Aerial Mounted Sensor and Controller for Heating Cable



## Features

### Type

- 2-in-1 sensor and controller.
- Precipitation sensor on top of unit.
- Temperature sensor below the unit.

### Color

- Standard : grey.

### Power

- 100-277V, 50/60 Hz.

### Rating

- 30A at 277VAC, 20A at 28VDC.

### Construction

- NEMA 3R rated enclosure, for outdoor installation.

### Control

- Dry contact relay output, NO (normally open).

### Trigger temperature range

- 1 °C (34 °F) to 6 °C (44 °F).

### Display

- Power and activation light indicator.

### Mode

- Control switch on the side of the unit to select operating mode: manual, automatic or standby/reset.

### Installation

- Screw 3/4" base conduit hub onto free-standing conduit, or use mounting holes in each corner of the enclosure for wall mounting.
- Install controller in a clear space that will receive precipitations.

*Note: It is recommended to mount a weatherproof junction box below the controller to make electrical connections.*

### Other feature

- Adjustment of drying cycle timer (DELAY OFF).
- Adjustment of precipitation sensor sensitivity (SENSITIVITY).

### Warranty

- 2-year warranty against defects.

### Application

- For controlling snow melting heating cable OWS series.
- Residential driveway, sidewalk, access ramp, underground parking ramp, roof and gutter.

## Models

Product # Kit	Price	Description	Amp.	Volts
DS-2C <sup>1</sup>	942.00	Aerial mounted sensor and controller to detect humidity and temperature	30A	277VAC
DS-8C <sup>1</sup>	1010.00	Aerial mounted controller with a sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 30A, 100V to 277V	1010.00	28VDC
DS-9C <sup>1</sup>	1010.00	Aerial mounted controller with a sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 2 X 30A, 100V to 277V		
EX-50	272.00	50 ft. (15 m) extension kit, with connection fittings for humidity sensor		
CDP-2	308.00	Interior controller and display for DS products		

<sup>1</sup> Requires a ground fault circuit interrupter (GFCI) in the electrical panel.



DS-2C



DS-8C



DS-9C



EX-50



CDP-2