

OCL Standard Convactor



Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, aluminum, semi-gloss black, metallic charcoal, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 60 Hz, 1-phase.

Construction

- 20-gauge steel.
- Top warm air outlet for rapid, even heat distribution throughout the room and optimum efficiency.
- Openings preventing insertion of foreign objects.
- High-limit temperature control with automatic reset.

Heating element

- 2 stainless steel tubular heating elements with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

Watt density

- 700W/ft. (2320W/m).

Control

- Built-in non programmable electronic thermostat for the 120V to 240V models (-TH models).
- Wall thermostat (not included).

Installation

- 4 in. (102 mm) minimum clearance to floor and from an adjacent wall.
- Quick surface-mounted installation, with the included wall mounting bracket.
- Single-screw built-in wire holder for quick access to the junction box.
- Optional kit of 10 BX wire-holding plates, for installing an AC90 type electrical cable.

Warranty

- 5-year warranty against defects.

Ouellet highly recommends the use of an electronic wall thermostat for greater comfort.

Application

- Kitchen, living room, family room, office, bedroom, basement, entrance hall.

Models

Volts	Watts	Product #		Length		Weight	
		Without thermostat	Built-in thermostat	in.	mm	lb	kg
120	500	OCU0502BL	OCU0502BL-TH	18	457	13	6
120	1000	OCU1002BL	OCU1002BL-TH	23 9/16	598	16.7	7.6
120	1500	OCU1502BL	OCU1502BL-TH	29 1/16	739	20	9.12
208	500	OCU0508BL	OCU0508BL-TH	18	457	13	6
208	1000	OCU1008BL	OCU1008BL-TH	23 9/16	598	16.7	7.6
208	1500	OCU1508BL	OCU1508BL-TH	29 1/16	739	20	9.12
208	2000	OCU2008BL	OCU2008BL-TH	34 5/8	880	24	10.9
240/208	500/375	OCU0500BL	OCU0500BL-TH	18	457	13	6
240/208	1000/750	OCU1000BL	OCU1000BL-TH	23 9/16	598	16.7	7.6
240/208	1500/1125	OCU1500BL	OCU1500BL-TH	29 1/16	739	20	9.12
240/208	2000/1500	OCU2000BL	OCU2000BL-TH	34 5/8	880	24	10.9
277	500	OCU0577BL	-	18	457	13	6
277	1000	OCU1077BL	-	23 9/16	598	16.7	7.6
277	1500	OCU1577BL	-	29 1/16	739	20	9.12
277	2000	OCU2077BL	-	34 5/8	880	24	10.9
480	1000	OCU1004BL	-	23 9/16	598	16.7	7.6
480	1500	OCU1504BL	-	29 1/16	739	20	9.12
480	2000	OCU2004BL	-	34 5/8	880	24	10.9

Options

Product # Kit	Product # Factory installed*	Description
KIT-SERF-BX	-	Kit of 10 BX wire-holding plates, for installing an AC90 type electrical cable
KIT-OCL-TRIAC-347	TRIAC	Single-pole electronic relay, coil 24V, without transformer: 15A at 347V max.
KIT-OCL-TRIAC-347T	TRIAC T	Single-pole electronic relay, coil 24V, with transformer: 15A at 208V, 240V, 277V, 347V
KIT-OCL-TRIAC-600	TRIAC	Single-pole electronic relay, coil 24V, without transformer: 6A at 600V max.

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.
Standard color is white.
Other voltages available upon request.

