

# OTH3000, 4000, 5007

Non Programmable Electronic Thermostats



# OTH3000P, 4000P

Programmable Electronic Thermostats



CSA-C828-13  
Performance Standard  
(except OTH5007)

ICES-003 Standard  
Compliant  
(except OTH5007)

## Features

### Type

- Electronic proportional pulsing line voltage thermostat.

### Color

- Standard: white.

### Voltage

- OTH3000-A, OTH4000-A, OTH3000P-A and OTH4000P-A:  
120/208/240V, 50/60 Hz.
- OTH5007: 277/347V, 50/60 Hz.

### Rating

- Maximum load:
  - OTH3000-A and OTH3000P-A: 12.5A at 120/208/240V.
  - OTH4000-A and OTH4000P-A: 16.7A at 120/208/240V.
  - OTH5007: 14.4A at 277/347V.
- Minimum load: 1.25A at 120/208/240/277/347V.

### Control

- 10-minute cycle (fan-forced convector) or 15-second cycle (convector).
- Resolution: 0.5 °C (1 °F).
- Precision:  $\pm 0.15$  °C (0.27 °F) on 15-second cycle.
- Precision:  $\pm 0.5$  °C (0.1 °F) on 10-minute cycle.

### Temperature range

- 5 °C (41 °F) to 30 °C (86 °F).

### Display

- Digital screen with white LED backlit (except OTH5007).
- Display fan-forced heater mode and keypad lock (when activated).
- Choice of temperature display format (°C or °F) and for programmable thermostats, time format (24h or 12h).

### Other feature

- Temperature setpoints recorded permanently in case of a power outage.
- Ability to set minimum and maximum setpoints.
- Night light mode for the display LED (except OTH5007).

### Installation

- 2-wire thermostat, easy to install.
- OTH5007 : Not compatible with a product equipped with a transformer.

### Application

- Baseboard heater, radiant ceiling, convactor and fan-forced convactor.

### Warranty

- 3-year warranty against defects.

## Features OTH3000P, 4000P

### Program

- Programming available for up to 4 periods a day.

### Mode

- Automatic, Manual, Economy.

### Other feature

- Early start of the heating period.

## Models

| Product #  | Price  | Description  | Watts          | Volts       |
|------------|--------|--|----------------|-------------|
| OTH3000-A  | 53.00  | Non programmable electronic proportional pulsing line voltage thermostat | 1500/2600/3000 | 120/208/240 |
| OTH4000-A  | 65.00  |  | 2000/3465/4000 | 120/208/240 |
| OTH5007    | 134.00 |  | 4000/5000      | 277/347     |
| OTH3000P-A | 78.00  | Programmable electronic proportional pulsing line voltage thermostat     | 1500/2600/3000 | 120/208/240 |
| OTH4000P-A | 89.00  |  | 2000/3465/4000 | 120/208/240 |

Standard color is white.