

OVR Register Wall Fan Heater



With Surface
Mounting Box and
Thermostat

Recessed with Thermostat



Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 1-phase.

Construction

- 20-gauge steel.
- High-limit temperature control with automatic reset.

Fan

- Quiet fan operating.
- 500W to 1000W; 40 cfm fan and 1250W to 2000W; 80 cfm fan.
- Factory-lubricated motor.

Heating element

- Durable tubular heating element with fins.
- Factory sealed element upon request.

Control

- Built-in thermostat available with a control knob or tamperproof.

Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.

Installation

- The air outlet should be installed at least 10 in. (25.4 cm) above floor.
- Quick installation with recess box mounting holes.
- Large wiring compartment.
- May be recessed in 2 in. x 3 in. stud partitions.
- Surface mounting box available.
- Tight fit with V-shaped recess box.

Warranty

- 5-year warranty against defects.

Application

- Entrance way, kitchen, bathroom, family room, basement.

OVR Models

Product #	Volts	Watts	Weight	
			lb	kg
OVRU0502	120	500	9.0	4.1
OVRU0752	120	750	9.0	4.1
OVRU1002	120	1000	9.0	4.1
OVRU1252	120	1250	9.0	4.1
OVRU1502	120	1500	9.0	4.1
OVRU0500	240/208	500/375	9.0	4.1
OVRU0750	240/208	750/563	9.0	4.1
OVRU1000	240/208	1000/750	9.0	4.1
OVRU1250	240/208	1250/938	9.0	4.1
OVRU1500	240/208	1500/1125	9.0	4.1
OVRU2000	240/208	2000/1500	9.0	4.1
OVRU2008	208	2000	9.0	4.1

Options

Product # Kit	Product # Factory installed*	Description
KIT-OVR-BS	-	Surface mounting box
KIT-OVR-DIS ³	DIS ³	Disconnect switch, 20A at 277V max.
-	ES ¹	With sealed element factory installed
KIT-OVR-TB6	TB6	Single-pole bi-metal thermostat
KIT-OVR-TB26 ²	TB26 ²	Double-pole bi-metal thermostat
KIT-OVR-TB6-AV	TB6AV	Single-pole bi-metal thermostat, tamperproof
KIT-OVR-TB26-AV ²	TB26AV ²	Double-pole bi-metal thermostat, tamperproof

* For factory installed options, add the option number to the product number. See the Product Code section inside the front cover.

¹ The option "sealed element" increases the reliability of these in humid environments. It does not completely eliminate the leakage currents of metal sheathed heating elements.

² "Off" position.

³ For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

Add "BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section.

