

OCC-WB Unit Heater with Bracket



Grounded 3-Pronged Outlet



NEMA 6-20R
20A, 250VAC



NEMA 6-30R
30A, 250VAC

Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electrical cable and as attach point for the bracket.
- 6 ft. (2 m) molded electrical cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset.

Fan

- Enclosed motor permanently lubricated.
- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Temperature rise

- 28 °C (51 °F).

Control

- Built-in thermostat included.

Installation ¹

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.
- 4000W must be plugged into a grounded 3-pronged outlet, 20A, 240VAC.
- 4800W must be plugged into a grounded 3-pronged outlet, 30A, 240VAC.

Warranty

- 3-year warranty against defects.

Application

- Workshop, shed, garage.

Models

Product #	Volts	Watts	Motor type	Grounded 3-Pronged Outlet	Weight	
					lb	kg
OCCU4000AMWB-MF-TB6 ¹	240/208	4000/3000	Enclosed	20A, 240VAC	16.0	7.3
OCCU4800AMWB-MF-TB6 ¹	240/208	4800/3600	Enclosed	30A, 240VAC	16.0	7.3

¹ Always unplug heater when not in use.
Standard color is almond.

