

OHV-CC Commercial Portable Unit Heater



Features

Color

- Standard: red and black.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1 phase.

Construction

- Positive off, double-pole, single-throw thermostat.
- Fan on/auto switch.
- Two level finger tip - high/low heat selector switch.
- Manual-reset over temperature protector.
- Specially designed outlet diffuser prevents foreign objects from entering heater.
- 18 and 20 gauge steel.
- Motor - totally enclosed - thermally protected.
- Draw-through design permits greater heat transfer.

Installation

- Versatile stand for floor or wall mount.
- Adjustable bracket/knobs allows all angle rotation.
- 20A cordset (NEMA 6-20P) on 4kW heater.
- 30A cordset (NEMA 6-30P) on 5kW heater.

Warranty

- 1-year warranty against defects.

Application

- Construction job site, garage, workshop, unheated area.

Models

Product # ¹	Volts	Phase	kW	Amp.	Air Flow		Temperature Rise		Weight		Plug
					fpm	cfm	°C	°F	lb	kg	
OHVU04000ROCC-F1-HL-T5	240/208	1	4/3	16.7/14.4	800	310	23	41	42	19	NEMA 6-20P
OHVU05000ROCC-F1-HL-T5	240/208	1	5/3.75	20.8/18	800	310	28	51	42	19	NEMA 6-30P

¹ Units come standard with hi-lo heat setting, fan only switch, integral thermostat and combination wall/ceiling/floor mounting bracket. Standard color is red and black.

